

## Streetmaster L-F

PU suction hose for streetcleaning machines. Abrasion, vacuum & microbe resistant



### Material

spiral: encapsulated PVC spring steel wire  
wall: polyester polyurethane, microbe resistant  
Film thickness between spirals approx. 0.7mm

### Applications

- Suction and wander hose for street cleaning machines and precinct sweeping machines
- Leaf collecting
- Grass cutting machines

### Properties

- microbe resistant
- extremely abrasion resistant
- UV and Ozone resistant
- highly flexible
- compressibility approx 3:1
- lightweight

### Temperature Range

- 0°C to +70°C
- peaks to +80°C

## Streetmaster L-F

DN	op. pressure c. bar	vacuum c. mmWG	bend radius c. mm	outer Ø c. mm	weight c. kg/m	article no.	stock length
100	0.50	1000	75	112	0.70	313-100-1000	/
125	0.40	1000	90	135	1.00	313-125-1000	/
150	0.35	750	100	160	1.20	313-150-1000	/
160	0.35	750	105	170	1.40	313-160-1000	/
180	0.30	750	120	192	1.50	313-180-1000	/
200	0.25	750	125	212	1.60	313-200-1000	/
225	0.25	700	150	240	1.80	313-225-1000	/
250	0.22	650	200	265	1.90	313-250-1000	/
300	0.20	600	250	315	3.00	313-300-1000	/


All data refers to an ambient temperature of +20 °C  
 Manufactured to order, lead time approx' 7 days.  
 Available on request in other lengths and sizes.  
 Subject to technical changes and colour deviations.



Master-Grip Hose Clamp,  
screwable



Master-Grip Quick-Fix  
Clamp



Hose Connector



Hose Reducer,  
symmetrical